

# MaxSave Street Light MAX-LD-308



Watt	Rectangular-Bulb Dimension WxDxH(mm)	Luminous Flux (LM)	Luminous Efficiency Lm/W	Color Temperarute (K)	Fixture Dimension WxDxH(mm)
80W	250x210x85	6,400	75-80	2700K 4100K 5000K 6400K	760×280×560
100W	250x210x85	8,000	75-80		
120W	315x275x85	10,200	80-85		
150W	335x290x85	12,750	80-85		
200W	350x315x90	17,000	80-85		

Category	Induction Street Light
Power	80W-200W
Light Source	Circular Induction Lamp
Lifespan	60,000-100,000 hours
High Power Factor	0.98
Working Voltage	AC 100V-300V
Working Temp.	-25°C to +50°C
Material	<ol style="list-style-type: none"> <li>1.The fixture body is made of high pressure die-casting Alu</li> <li>2.High-intensity, high temperature resistant cambered tempered glass</li> <li>3.Once shaping high-purity aluminum reflector provides optimum light distribution</li> <li>4.Electrostatic spray surface treatment technology</li> <li>5.Match circular induction lamp with its excellent Color Rendering Index and light efficiency, long life span, no flicker and energy saving, wide range of color temperature and soft light ,stable light output.</li> </ol>
Applications	Roads, streets, highways,viaducts,bridges and other lighting areas