

# MaxSave Street Light MAX-LD-313



Watt	Rectangular Bulb Dimension WxDxH(mm)	Luminous Flux (LM)	Luminous Efficiency Lm/W	Color Temperarute (K)	Fixture Dimension WxDxH(mm)
40W	200x110x80	3,000	70-75	2700K-6400K	600x370x160
60W		4,500	70-75		

Category	Induction Street Light
Power	40W-60W
Light Source	Circular Induction Lamp
Lifespan	60,000-100,000 hours
High Power Factor	0.98
Working Voltage	AC 100V-300V
Working Temp.	-25°C to +50°C
Protection Class	IP 65
Anti-Cossosion Class	WF1
Material	<ol style="list-style-type: none"> <li>1.The fixture body and Electrical box are made of die-casting Alu</li> <li>2.High-intensity, High temperature resistant cambered tempered glass</li> <li>3.Once shaping high-purity aluminum reflector provides optimum light distribution</li> <li>4.Electrostatic spray surface treatment technology</li> <li>5.Separate installation of Ballast and light source is more convenient for heat dissipation</li> <li>6.Match rectangular induction lamp with its excellent Color Rendering Index and light efficiency, long life span, no flicker and energy saving, wide range of color temperature and soft light to stable light output</li> </ol>
Applications	Roads, streets, highways,viaducts,bridges and other lighting areas